



GADO

David[®]

daidsuperlight.dk

Art.No.	Type
710-31A-235	GADO bollard fitting excl TOWER pole. LEDstrip 12W/830. Clear PC-screen. CL.I. Hot galvanized steel.
710-31A-245	GADO bollard fitting excl TOWER pole. LEDstrip 12W/840. Clear PC-screen. CL.I. Hot galvanized steel.
710-31A-C35	GADO bollard fitting excl TOWER pole. LEDstrip 12W/830. Clear PC-screen. CL.I. Cor-ten.
710-31A-C45	GADO bollard fitting excl TOWER pole. LEDstrip 12W/840. Clear PC-screen. CL.I. Cor-ten.
710-31A-935*	GADO bollard fitting excl TOWER pole. LEDstrip 12W/830. Clear PC-screen. CL.I. Black RAL9005.*
710-31A-945*	GADO bollard fitting excl TOWER pole. LEDstrip 12W/840. Clear PC-screen. CL.I. Black RAL9005.*

Additional charge for protection class II double insulated. Prepared for fuse inset.

Accessories:

890-701-200	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-701-C00	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-701-900*	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
890-981-200	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-981-C00	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-981-900*	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
920-650-200	TOWER foundation f/burial. 190x190x500mm. Hot galvanized.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
924-100-012	Fuse inset for Ø108/Ø133mm poles.

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

Variation options:
 • Light output from the luminaire: 1113-1171Lm.

- Key features:
- 10 year anti-corrosion warranty (hot galvanized).
 - 10 year reorder warranty.
 - 5 year LED & driver warranty.
 - Life expectancy: 100.000 hours.
 - Integrated 6/10 kV surge protection.

