

Art.No.	Type
155-415-245-K2	HANS spot. Fortimo SLM 15W/840. CL.II. Clear PC-Lens. Hot galvanized steel.
155-415-945-K2*	HANS spot. Fortimo SLM 15W/840. CL.II. Clear PC-Lens. Black RAL9005.*
155-420-245-K2	HANS spot. Fortimo SLM 20W/840. CL.II. Clear PC-Lens. Hot galvanized steel.
155-420-945-K2*	HANS spot. Fortimo SLM 20W/840. CL.II. Clear PC-Lens. Black RAL9005.*
155-432-245-K2	HANS spot. Fortimo SLM 32W/840. CL.II. Clear PC-Lens. Hot galvanized steel.
155-432-945-K2*	HANS spot. Fortimo SLM 32W/840. CL.II. Clear PC-Lens. Black RAL9005.*

Accessories:

920-831-200	Pole Ø60-Ø95 bracket side mounting f/HANS spot. Hot galvanized steel.
920-831-900*	Pole Ø60-Ø95 bracket side mounting f/HANS spot. Black RAL9005.*
920-833-200	Bollard bracket Ø133mm f/HANS spot. Topmounting. Hot galvanized steel.
920-833-900*	Bollard bracket Ø133mm f/HANS spot. Topmounting. Black RAL9005.*
880-120-200	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Hot galvanized steel.
880-120-900*	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Black RAL9005.*
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
831-10-N-12-2	Square pole 1,20/0,70M f/burial. Coat hanger and turn securing welded. Hot galvanized steel.
831-10-N-12-9*	Square pole 1,20/0,70M f/burial. Coat hanger and turn securing welded. Black RAL9005.*

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.


Note: The spot base is excl. accessories.

Variation options:

- Also available with 3000K.
- Light output from the luminaire: 1281-2984Lm.

Key features:

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated 6/10 kV surge protection.



Spot + bracket side + Ø60mm pole.

Spot + bollard bracket + Ø133mm pole.

Spot + square pole incl. coat hanger og turn securing.

