

Art nr.	Type
<b>220-100-205</b>	HENRIK bollard fitting excl pole. E27. Clear PC-screen. CL.I. Hot galvanized steel.
<b>220-100-305</b>	HENRIK bollard fitting excl pole. E27. Clear PC-screen. CL.I. Solid copper.
<b>220-100-905*</b>	HENRIK bollard fitting excl pole. E27. Clear PC-screen. CL.I. Black RAL9005.* Additional charge for protection class II double insulated.

**Recommended Light Sources:**

<b>982-70-09-03</b>	Philips CorePRO LEDbulb ND 7,5-60W. E27. A60. 15000h. 806Lm. 3000K.
<b>982-70-09-04</b>	Philips CorePRO LEDbulb ND 7,5-60W. E27. A60. 15000h. 806Lm. 4000K.

**Accessories:**

<b>880-120-200</b>	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Hot galvanized steel.
<b>880-120-300</b>	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Solid copper.
<b>880-120-900*</b>	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Black RAL9005.* Additional charge for pole for class II bollard fittings. Delivered with mounting hatch. See page 110.
<b>800-145-500</b>	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
<b>920-634-200</b>	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
<b>800-13-133-2</b>	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
<b>800-13-133-9*</b>	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Black RAL9005.*
<b>920-67-220-18</b>	Cover screen 180°. Hot galvanized plate. (Also available in 120°) ----- Several variations of poles, accessories and spare parts. See page 103-130 -----

\*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

**Variation options:**

- Also available with opal white PC-screen.
- Also available with clear or opal glass.

**Key features:**

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- Easy light source change and great flexibility with retrofit LED.

