

Art.No.	Type
350-302-206	MACON G2 bollard fitting excl TOWER pole. E27. Satine acrylic-screen. CL.I. Hot galvanized steel.
350-302-C06	MACON G2 bollard fitting excl TOWER pole. E27. Satine acrylic-screen. CL.I. Cor-ten.
350-302-906*	MACON G2 bollard fitting excl TOWER pole. E27. Satine acrylic-screen. CL.I. Black RAL9005.* Additional charge for protection class II double insulated. Prepared for fuse inset.

Recommended Light Sources:

982-70-11-03	Philips CorePRO LEDbulb ND 10,5-75W. E27. A60. 15000h. 1055Lm. 3000K.
982-70-11-04	Philips CorePRO LEDbulb ND 10-75W. E27. A60. 15000h. 1055Lm. 4000K.

Accessories:

890-701-200	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-701-C00	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-701-900*	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
890-981-200	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-981-C00	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-981-900*	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
920-650-200	TOWER foundation f/burial. 190x190x500mm. Hot galvanized.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
924-100-012	Fuse inset for Ø108/Ø133mm poles.
920-67-350-18	Cover screen 180°. Hot galvanized plate. (Also available in 120°)

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

Key features:

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- Easy light source change and great flexibility with retrofit LED.

