

Ø133mm poles for bollard- & park fittings f/burial. CL.II.

Art.No.	Type
880-121-200	Ø133mm pole. 1,20/0,70M f/burial. CL.II. w/mounting hatch. Hot galvanized steel.
880-121-900*	Ø133mm pole. 1,20/0,70M f/burial. CL.II. w/mounting hatch. Black RAL9005.*
880-151-200	Ø133mm pole. 1,50/1,00M f/burial. CL.II. w/mounting hatch. Hot galvanized steel.
880-151-900*	Ø133mm pole. 1,50/1,00M f/burial. CL.II. w/mounting hatch. Black RAL9005.*
880-201-200	Ø133mm pole. 2,00/1,40M f/burial. CL.II. w/mounting hatch. Hot galvanized steel.
880-201-900*	Ø133mm pole. 2,00/1,40M f/burial. CL.II. w/mounting hatch. Black RAL9005.*
880-251-200	Ø133mm pole. 2,50/1,90M f/burial. CL.II. w/mounting hatch. Hot galvanized steel.
880-251-900*	Ø133mm pole. 2,50/1,90M f/burial. CL.II. w/mounting hatch. Black RAL9005.*
880-301-200	Ø133mm pole. 3,00/2,40M f/burial. CL.II. w/mounting hatch. Hot galvanized steel.
880-301-900*	Ø133mm pole. 3,00/2,40M f/burial. CL.II. w/mounting hatch. Black RAL9005.*
880-351-200	Ø133mm pole. 3,50/2,90M f/burial. CL.II. w/mounting hatch. Hot galvanized steel.
880-351-900*	Ø133mm pole. 3,50/2,90M f/burial. CL.II. w/mounting hatch. Black RAL9005.*
880-451-200	Ø133mm pole. 4,80/4,00M f/burial. CL.II. w/mounting hatch. Hot galvanized steel.
880-451-900*	Ø133mm pole. 4,80/4,00M f/burial. CL.II. w/mounting hatch. Black RAL9005.*

Accessories:

800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
924-100-012	Fuse inset for Ø108/Ø133mm poles. 1 neozed fuse.
800-13-133-2	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
800-13-133-9*	Bracket f/OPUS74 outlet (excl). Fits t/Ø60mm pole. Black RAL9005.*
923-100-010	Mounting plate for fuse insert. Used for CL.II fittings.

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

	A	B	C	D
Pole 1,20/0,70M	1200	700	133	40
Pole 1,50/1,00M	1500	1000	133	40
Pole 2,00/1,40M	2000	1400	133	100
Pole 2,50/1,90M	2500	1900	133	390
Pole 3,00/2,40M	3000	2400	133	390
Pole 3,50/2,90M	3500	2900	133	390

