

Art.No.	Type
553-35B-245-K2	OskarLED bollard fitting excl TOWER pole. LEDstrip 13W/830. Clear PC-screen. CL.II. Hot galvanized steel.
553-35B-245-K2	OskarLED bollard fitting excl TOWER pole. LEDstrip 13W/840. Clear PC-screen. CL.II. Hot galvanized steel.
553-35B-935-K2*	OskarLED bollard fitting excl TOWER pole. LEDstrip 13W/830. Clear PC-screen. CL.II. Black RAL9005.*
553-35B-945-K2*	OskarLED bollard fitting excl TOWER pole. LEDstrip 13W/840. Clear PC-screen. CL.II. Black RAL9005.*

Additional charge for protection class II double insulated. Prepared for fuse inset.

Accessories:

890-701-200	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-701-900*	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
890-981-200	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-981-900*	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
920-650-200	TOWER foundation f/burial. 190x190x500mm. Hot galvanized.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
553-100-200	Protective screen f/OskarLED. Against vandalism. Hot-dip galvanized steel.
924-100-012	Fuse inset for Ø108/Ø133mm poles.

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

Variation options:

- Light output from the luminaire: 425-447Lm.

Key features:

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated 6/10 kV surge protection.

