

Art.No.	Type
553-13B-235-K2	OskarLED bollard fitting excl pole. LEDstrip 13W/830. Clear PC-screen. CL.II. Hot galvanized steel.
553-13B-245-K2	OskarLED bollard fitting excl pole. LEDstrip 13W/840. Clear PC-screen. CL.II. Hot galvanized steel.
553-13B-935-K2*	OskarLED bollard fitting excl pole. LEDstrip 13W/830. Clear PC-screen. CL.II. Black RAL9005.*
553-13B-945-K2*	OskarLED bollard fitting excl pole. LEDstrip 13W/840. Clear PC-screen. CL.II. Black RAL9005.*

Additional charge for protection class II double insulated.

Accessories:

880-121-200	Ø133mm pole f/burial. 1,20/0,70M w/mounting hatch. CL. II. Hot galvanized steel.
880-121-900*	Ø133mm pole f/burial. 1,20/0,70M w/mounting hatch. CL.II. Black RAL9005.*
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
920-100-012	Fuse inset for Ø108/Ø133mm poles.
800-13-133-2	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
800-13-133-9*	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Black RAL9005.*
553-100-200	Protective screen f/OskarLED. Against vandalism. Hot-dip galvanized steel.

----- Several variations of poles, accessories and spare parts. See page 103-130 -----

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.
 Note: OskarLED in Anthracite RAL7016 is called ZENTA and is no longer exclusive through www.solar.dk

Variation options:
 • Light output from the luminaire: 425-447Lm.

Key features:
 • 10 year anti-corrosion warranty (hot galvanized).
 • 10 year reorder warranty.
 • 5 year LED & driver warranty.
 • Life expectancy: 50.000 hours.
 • Integrated 6/10 kV surge protection.

