


CE LED IP56 230V IK10   CLO

OskarLED

David® 

daidsuperlight.dk 

**Art.No.**      **Type**

<b>553-34B-245-K2</b>	OskarLED park fitting excl pole. LEDstrip 35W/840. CL.II. Clear PC-screen. Hot galvanized steel.
<b>553-34B-945-K2*</b>	OskarLED park fitting excl pole. LEDstrip 35W/840. CL.II. Clear PC-screen. Black RAL9005.*
<b>+ PROG01</b>	Dimmer profil 01 = ON/OFF without dimming
<b>+ PROG07</b>	Dimmer profil 07 = 60% 20:00-22:00, 40% 22:00-05:00, 60% 05:00-06:00 (stepdimmer). See other dimming profiles on page 100.

**Accessories:**

<b>880-301-200</b>	Ø133mm cylindrical pole LPH 2,40M f/burial. 3,00/2,40M. Hot galvanized steel.
<b>880-301-900*</b>	Ø133mm cylindrical pole LPH 2,40M f/burial. 3,00/2,40M. Black RAL9005.*
<b>800-145-500</b>	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
<b>920-634-200</b>	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
<b>924-100-012</b>	Fuse inset for Ø108/Ø133mm poles.
<b>800-13-133-2</b>	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
<b>800-13-133-9</b>	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Black RAL9005.*

----- Several variations of poles, accessories and spare parts. See page 103-130 -----

\*Powder coated:      The standard color is Black RAL9005. Other RAL colors on request with extra price.

**Variation options:**

- Available with 3000K.
- Possibility of project-adapted configuration.
- Light output from the luminaire: 2246Lm.

**Key features:**

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated 6/10 kV surge protection.
- Supplied with 3,5M cable.

