

CE

LED

IP56

230V

IK10



THORminiLED

David®

davidsuperlight.dk



Art.No.	Type
551-112-235	THORminiLED bollard fitting excl pole. DLM ES 10W/830. Clear PC-Screen. CL.I. Hot galvanized steel.
551-112-245	THORminiLED bollard fitting excl pole. DLM ES 10W/840. Clear PC-Screen. CL.I. Hot galvanized steel.
551-112-935*	THORminiLED bollard fitting excl pole. DLM ES 10W/830. Clear PC-Screen. CL.I. Black RAL9005.*
551-112-945*	THORminiLED bollard fitting excl pole. DLM ES 10W/840. Clear PC-Screen. CL.I. Black RAL9005.*
551-122-235	THORminiLED bollard fitting excl pole. DLM ES 18W/840. Clear PC-Screen. CL.I. Hot galvanized steel.
551-122-245	THORminiLED bollard fitting excl pole. DLM ES 18W/840. Clear PC-Screen. CL.I. Hot galvanized steel.
551-122-935*	THORminiLED bollard fitting excl pole. DLM ES 18W/830. Clear PC-Screen. CL.I. Black RAL9005.*
551-122-945*	THORminiLED bollard fitting excl pole. DLM ES 18W/840. Clear PC-Screen. CL.I. Black RAL9005.*

Additional charge for protection class II double insulated.

Accessories:

880-120-200	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Hot galvanized steel.
880-120-900*	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Black RAL9005.* Additional charge for pole for class II bollard fittings. Delivered with mounting hatch. See page 110.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
800-13-133-2	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
800-13-133-9*	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Black RAL9005.*
920-67-5511-18	Cover screen 180°. Hot galvanized plate. (Also available in 120°)
000-299-900	Surge protector >10 kV. ----- Several variations of poles, accessories and spare parts. See page 103-130 -----

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

Variation options:

- Light output from the luminaire: 730-1565Lm.

Key features:

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- 5 year LED warranty.
- 230V LED module. No driver.
- Life expectancy: 50.000 hours.

