

TOWER pole for TOWER fittings. Bolting or for burial. CL. II.

Art.No.	Type
890-701-200	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-701-C00	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-701-900*	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
890-981-200	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-981-C00	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-981-900*	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*

Accessories:

920-650-200	TOWER foundation f/burial. 190x190x500mm. Hot galvanized.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
924-100-012	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
924-100-012	Fuse inset for Ø108/Ø133mm poles.
000-299-900	Surge protector 10 kV.

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

