



TØRRING

David®

daidsuperlight.dk 

Art.No.	Type
158-617-236	TØRRING ceiling fixture. CLE 7W/830. Opal white PC-screen. Hot galvanized steel.
158-617-246	TØRRING ceiling fixture. CLE 7W/840. Opal white PC-screen. Hot galvanized steel.
158-617-936*	TØRRING ceiling fixture. CLE 7W/830. Opal white PC-screen. Black RAL9005.*
158-617-946*	TØRRING ceiling fixture. CLE 7W/840. Opal white PC-screen. Black RAL9005.*
158-610-236	TØRRING ceiling fixture. CLE 10W/830. Opal white PC-screen. Hot galvanized steel.
158-610-246	TØRRING ceiling fixture. CLE 10W/840. Opal white PC-screen. Hot galvanized steel.
158-610-936*	TØRRING ceiling fixture. CLE 10W/830. Opal white PC-screen. Black RAL9005.*
158-610-946*	TØRRING ceiling fixture. CLE 10W/840. Opal white PC-screen. Black RAL9005.*

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

Note: Can be turned in 2 different ways. See drawing below and TØRRING wall on page 38. See the back plate/mounting sketch under the product at daidsuperlight.com

Variation options:

- Light output from the luminaire: 426-691Lm.

Key features:

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated 2 kV surge protection.

