



Art.No.	Type
158-417-236	TØRRING wall fixture. CLE 7W/830. Opal white PC-screen. Hot galvanized steel.
158-417-246	TØRRING wall fixture. CLE 7W/840. Opal white PC-screen. Hot galvanized steel.
158-417-936*	TØRRING wall fixture. CLE 7W/830. Opal white PC-screen. Black RAL9005.*
158-417-946*	TØRRING wall fixture. CLE 7W/840. Opal white PC-screen. Black RAL9005.*
158-410-236	TØRRING wall fixture. CLE 10W/830. Opal white PC-screen. Hot galvanized steel.
158-410-246	TØRRING wall fixture. CLE 10W/840. Opal white PC-screen. Hot galvanized steel.
158-410-936*	TØRRING wall fixture. CLE 10W/830. Opal white PC-screen. Black RAL9005.*
158-410-946*	TØRRING wall fixture. CLE 10W/840. Opal white PC-screen. Black RAL9005.*

Accessories:

- 920-158-900* Decorative plate f/TØRRING.
Decorative plate f/TØRRING available in other designs on request.

999husnr. House number. (When purchasing a minimum of 20 pcs.)

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

Note: Can be turned in 2 different ways. See drawing below and TØRRING ceiling fixture on page 11. See the back plate/mounting sketch under the product at davidsuperlight.com

Variation options:

- Light output from the luminaire: 426-691Lm.

Key features:

- 10 year anti-corrosion warranty.
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated 2 kV surge protection.

