

CE LED IP56 230V IK10



WEKA

David®

davidsuperlight.dk 

Art.No.	Type
636-31A-245	WEKA bollard fitting excl TOWER pole. DLM ES 10W/840. Clear PC-screen. CL.I. Hot galvanized steel.
636-31A-C45	WEKA bollard fitting excl TOWER pole. DLM ES 10W/840. Clear PC-screen. CL.I. Cor-ten.
636-31A-945	WEKA bollard fitting excl TOWER pole. DLM ES 10W/840. Clear PC-screen. CL.I. Black RAL9005.*
636-32A-245	WEKA bollard fitting excl TOWER pole. DLM ES 18W/840. Clear PC-screen. CL.I. Hot galvanized steel.
636-32A-C45	WEKA bollard fitting excl TOWER pole. DLM ES 18W/840. Clear PC-screen. CL.I. Cor-ten.
636-32A-945	WEKA bollard fitting excl TOWER pole. DLM ES 18W/840. Clear PC-screen. CL.I. Black RAL9005.*

Additional charge for protection class II double insulated. Prepared for fuse inset.

Accessories:

890-701-200	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-701-C00	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-701-900*	TOWER pole 0,70M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
890-981-200	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Hot galvanized steel.
890-981-C00	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Cor-ten.
890-981-900*	TOWER pole 0,98M w/mounting hatch. 145/200mm. CL.II. Black RAL9005.*
920-650-200	TOWER foundation f/burial. 190x190x500mm. Hot galvanized.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
924-100-012	Fuse inset for Ø108/Ø133mm poles.
920-67-6341-18	Cover screen 180°. Hot galvanized plate. (Also available in 120°)

*Powder coated: The standard color is Black RAL9005. Other RAL colors on request with extra price.

Variation options:

- Also available with 3000K.
- Light output from the luminaire: 964-1746Lm.

Key features:

- 10 year anti-corrosion warranty (hot galvanized).
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated 6/10 kV surge protection.

